





## **CSTD6**


Terminal Type - CSTD6 , Test Disconnect Terminal Blocks , nominal voltage: 800 V, nominal current: 38 A, connection method: Screw connection, number of connections: 2, Rated cross section : 6 mm<sup>2</sup> , cross section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS32

### **Product Accessories**

<b>DIN Rail Perforated</b>		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>End Clamp</b>		
SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
EPTD	Height : 50.00 mm Width : 2.50 mm Length : 65.00 mm	
<b>Insertion Bridge</b>		
ADSL-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm	

Insertion Bridge		
ADSL-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-7W	Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm	

Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	

Marker carriers		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	