

## **DPSC5.08WF-3W**

Terminal Type - DPSC5.08WF - 3W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 6, cross-section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, Rated cross-section - 2.5 mm<sup>2</sup>, mounting type: TS35/7.5 , TS35/15

### Product Accessories

<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.08	Pitch : 5.08 mm	
<b>Tool</b>		
DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	