


KUDT4-2X2

Terminal Type - KUDT4-2X2, Knife disconnect terminal block, nominal voltage: 800 V, nominal current: 20 A, Rated cross-section: 4.0 mm², connection method: Screw connection, number of connections: 4, cross-section: 0.5 mm² - 4 mm², mounting type: TS 35/7.5, TS 35/15

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

End Cover		
KPMD4	Height : 42.40 mm Width : 1.50 mm Length : 67.00 mm	

Insertion Bridge		
SLC4N-10W	Width : 58.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-3W	Width : 16.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-4W	Width : 22.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-5W	Width : 28.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-6W	Width : 34.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-2W	Width : 10.91 mm Pitch : 6.00 mm Length : 23.00 mm	

Marker For Terminal Blocks		
LABEL KN5.5	Width : 6.00 mm	

Partition Plate		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	