











## **KUT4N**

Terminal Type - KUT4N , Feed-through terminal block for photo voltaic applications , nominal voltage: 1000 V, nominal current: 32 A, connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> - 4 mm<sup>2</sup>, AWG: 20 - 10, mounting type: TS 35/7.5, TS 35/15 , TS 32

### Product Accessories

<b>Cover Profile</b>		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
<b>Cover Profile Carrier</b>		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
<b>DIN Rail Perforated</b>		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
<b>DIN Rail, Unperforated</b>		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	

<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
KPXN	Height : 41.50 mm Width : 1.50 mm Length : 41.50 mm	
<b>Fixed Bridge</b>		
CCLA4N-10W	Height : 17.00 mm Pitch : 6.00 mm Length : 58.60 mm	
CCLA4N-3W	Height : 17.00 mm Pitch : 6.00 mm Length : 16.60 mm	
CCLA4N-4W	Height : 17.00 mm Pitch : 6.00 mm Length : 22.80 mm	

<b>Fixed Bridge</b>		
CCLA4N-5W	Height : 17.00 mm Pitch : 6.00 mm Length : 28.60 mm	
CCLA4N-2W	Height : 17.00 mm Pitch : 6.00 mm Length : 10.60 mm	
<b>Insertion Bridge</b>		
SLC4N-10W	Width : 58.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-3W	Width : 16.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-4W	Width : 22.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-5W	Width : 28.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-6W	Width : 34.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-2W	Width : 10.91 mm Pitch : 6.00 mm Length : 23.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.5	Width : 6.00 mm	
<b>Partition Plate</b>		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	

Spacer Plate		
SBN1	Height : 12.10 mm Width : 1.37 mm Length : 13.20 mm	
Switching Jumper		
LSR6N	Height : 22.20 mm Width : 5.00 mm	
RSLDD	Thickness : 1.20 mm Pitch : 6.00 mm Length : 11.00 mm	
Warning Label		
WL4	Height : 25.20 mm Thickness : 1.10 mm Length : 28.80 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	