










KUT50A

Terminal Type - KUT50A , Feed-through terminal block, Nominal voltage: 1000 V, Nominal current: 150 A, Connection method: Screw connection, Operated by: 5mm Allen Key, Number of connections: 2, cross section: 16 mm² - 50 mm², AWG: 2/0-6, width: 20.5 mm , length : 71 mm , height : 75.5 mm , mounting type: TS35/7.5 , TS35/15 , and TS32

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Fixed Bridge		
CCLA50-2W	Height : 25.00 mm Pitch : 20.50 mm Length : 37.00 mm	
CCLA50-3W	Height : 25.00 mm Pitch : 20.50 mm Length : 57.50 mm	
CCLA50-5W	Height : 25.00 mm Pitch : 20.50 mm Length : 98.50 mm	
Marker For Terminal Blocks		
LABEL KN17	Width : 17.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
Tap Terminal		
KTT6	Height : 31.00 mm Width : 28.00 mm	