


KUT6

Terminal Type - KUT6 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 41 A, connection method: Screw connection, number of connections: 2, Rated cross section: 6.0 mm² , cross section: 0.5 mm² - 10 mm², AWG: 20 - 8, mounting type: TS35/7.5 , TS35/15 , TS32 and TS15

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier









UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	---









DIN Rail Perforated




CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPX	Height : 36.00 mm Thickness : 1.50 mm Length : 40.00 mm	
Fixed Bridge		
CCLA6-2W	Height : 20.00 mm Pitch : 8.00 mm Length : 13.50 mm	

Fixed Bridge			
CCLA6-10W	Height : 20.00 mm Pitch : 8.00 mm Length : 78.10 mm		
CCLA6-3W	Height : 20.00 mm Pitch : 8.00 mm Length : 21.60 mm		
CCLA6-4W	Height : 20.00 mm Pitch : 8.00 mm Length : 29.70 mm		
CCLA6-5W	Height : 20.00 mm Pitch : 8.00 mm Length : 37.70 mm		
CCLA6-6W	Height : 20.00 mm Pitch : 8.00 mm Length : 45.80 mm		
Insertion Bridge			
SLC6-10W	Width : 75.60 mm Pitch : 8.00 mm Length : 26.00 mm		
SLC6-3W	Width : 22.60 mm Pitch : 8.00 mm Length : 26.00 mm		
SLC6-4W	Width : 30.60 mm Pitch : 8.00 mm Length : 26.00 mm		
SLC6-5W	Width : 38.60 mm Pitch : 8.00 mm Length : 26.00 mm		
SLC6-6W	Width : 46.60 mm Pitch : 8.00 mm Length : 26.00 mm		
SLC6-2W	Width : 14.60 mm Pitch : 8.00 mm Length : 26.00 mm		

Marker For Terminal Blocks		
LABEL KN8	Width : 8.00 mm	
Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
KBX	Height : 43.00 mm Thickness : 1.50 mm Length : 54.00 mm	
Switching Jumper		
LSR2.5-6	Height : 23.00 mm Width : 5.00 mm	
RSL6	Thickness : 1.20 mm Pitch : 8.00 mm Length : 13.80 mm	
Warning Label		
WL6	Height : 28.00 mm Thickness : 1.10 mm Length : 31.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	