

KUTM2.5



Terminal Type - KUTM2.5 , Feed-through terminal block, nominal voltage: 800 V, nominal current: 24 A, connection method: Screw connection, number of connections: 2, Rated cross section: 2.5 mm² , cross section: 0.5 mm² – 4.0 mm², mounting type: TS35/7.5 , TS35/15 , TS32 and TS15


Product Accessories

Cover Profile		
PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
Cover Profile Carrier		
UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPNS	Height : 31.00 mm Thickness : 1.50 mm Length : 36.50 mm	
Fixed Bridge		
CCLK2.5-2W	Height : 14.30 mm Pitch : 5.00 mm Length : 9.40 mm	

Fixed Bridge		
CCLK2.5-4W	Height : 14.30 mm Pitch : 5.00 mm Length : 19.40 mm	
CCLK2.5-10W	Height : 14.30 mm Pitch : 5.00 mm Length : 49.40 mm	
CCLK2.5-3W	Height : 14.30 mm Pitch : 5.00 mm Length : 14.40 mm	
CCLK2.5-6W	Height : 14.30 mm Pitch : 5.00 mm Length : 29.40 mm	
Insertion Bridge		
SLC2.5N-2W	Width : 9.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-10W	Width : 49.20 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-3W	Width : 14.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-4W	Width : 19.60 mm Pitch : 5.00 mm Length : 23.00 mm	
SLC2.5N-5W	Width : 24.60 mm Pitch : 5.00 mm Length : 23.00 mm	
Marker For Terminal Blocks		
LABEL KN5	Width : 5.00 mm	

Partition Plate		
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm	
KBM	Height : 37.50 mm Thickness : 1.50 mm Length : 50.50 mm	

Warning Label		
WL2.5N	Height : 24.00 mm Thickness : 1.10 mm Length : 24.00 mm	

Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	