










## SGQ2.5-2X2



Terminal Type - SGQ2.5-2X2 , Multi Conductor Ground modular terminal block , connection method: Spring Cage Connection , number of connections: 4, Rated cross section: 2.5 mm<sup>2</sup>, cross section: 0.08 mm<sup>2</sup> - 4 mm<sup>2</sup> , AWG: 24-12, mounting type: TS 35/7.5, TS 35/15 , colour :Green-yellow

### Product Accessories

| DIN Rail Perforated    |                                                              |                                                                                       |
|------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |    |
| DIN Rail, Unperforated |                                                              |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |  |
| End Cap                |                                                              |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm    |  |
| End Clamp              |                                                              |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Length : 44.75 mm                       |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm    |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm   |  |
| DCKN                   | Height : 33.00 mm<br>Width : 6.00 mm<br>Length : 43.50 mm    |  |

| End Clamp                  |                                                            |                                                                                       |
|----------------------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| DCKN10                     | Height : 35.00 mm<br>Width : 10.00 mm<br>Length : 43.50 mm |    |
| SCKN                       | Height : 34.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |    |
| SCUN                       | Height : 35.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |    |
| End Cover                  |                                                            |                                                                                       |
| CSP2.5-2X2                 | Height : 22.70 mm<br>Width : 2.00 mm<br>Length : 74.70 mm  |    |
| Marker For Terminal Blocks |                                                            |                                                                                       |
| LABEL KN5                  | Width : 5.00 mm                                            |   |
| Partition Plate            |                                                            |                                                                                       |
| DBF-3                      | Height : 38.40 mm<br>Width : 3.00 mm<br>Length : 78.00 mm  |  |
| Plug-in Bridge/Jumper      |                                                            |                                                                                       |
| SLPU5-2W                   | Height : 26.00 mm<br>Width : 9.15 mm<br>Pitch : 5.00 mm    |  |
| SLPU5-3W                   | Height : 26.00 mm<br>Width : 14.15 mm<br>Pitch : 5.00 mm   |  |
| SLPU5-10W                  | Height : 26.00 mm<br>Width : 49.15 mm<br>Pitch : 5.00 mm   |  |
| SLPU5-4W                   | Height : 26.00 mm<br>Width : 19.15 mm<br>Pitch : 5.00 mm   |  |

| Plug-in Bridge/Jumper |                                                          |                                                                                     |
|-----------------------|----------------------------------------------------------|-------------------------------------------------------------------------------------|
| SLPU5-5W              | Height : 26.00 mm<br>Width : 24.15 mm<br>Pitch : 5.00 mm |  |
| SLPU5-6W              | Height : 26.00 mm<br>Width : 29.15 mm<br>Pitch : 5.00 mm |  |
| SLPU5-7W              | Height : 26.00 mm<br>Width : 34.15 mm<br>Pitch : 5.00 mm |  |

| Marker carriers |                                                            |                                                                                       |
|-----------------|------------------------------------------------------------|---------------------------------------------------------------------------------------|
| SCUDDMLH        | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm |    |
| SCUNMLH         | Height : 53.50 mm<br>Width : 9.50 mm<br>Length : 50.60 mm  |   |
| DCKNMLH         | Height : 45.50 mm<br>Width : 6.00 mm<br>Length : 43.50 mm  |  |
| SCKNMLH         | Height : 45.50 mm<br>Width : 8.00 mm<br>Length : 44.90 mm  |  |