

SPT120XL

Terminal Type - SPT120XL , High current connectors with secured hinged cover , nominal voltage: 1500 V, nominal current: 269 A, connection method: Bolt connection, Bolt with clinched conical ,number of connections: 2, cross section: 16 mm² - 120 mm² , width: 42 mm ,length: 225.7 mm , height : 80.3 mm , mounting type: TS 35/7.5 and TS 35/15

Product Accessories

DIN Rail Perforated		
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

Fixed Bridge		
CCLASPT150-2W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
CCLASPT150-3W	Width : 18.00 mm Thickness : 3.00 mm Pitch : 42.00 mm Length : 68.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Width : 12.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	