









## SPT70

Terminal Type - SPT70, High current connectors with secured hinged cover, nominal voltage: 1000 V, nominal current: 192 A, Rated cross-section -70 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 16 mm<sup>2</sup> - 70 mm<sup>2</sup>, AWG: 6 - 2/0, mounting type: TS 35/7.5, TS 35/15, colour : GREY

### Product Accessories

| DIN Rail Perforated    |                                                              |                                                                                       |
|------------------------|--------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |    |
| DIN Rail, Unperforated |                                                              |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm  |  |
| End Cap                |                                                              |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm    |  |
| End Clamp              |                                                              |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Length : 44.75 mm                       |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm   |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm    |  |

| Fixed Bridge               |                                                                                  |                                                                                      |
|----------------------------|----------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| CCLASPT70-2W               | Width : 15.00 mm<br>Thickness : 3.00 mm<br>Pitch : 32.00 mm<br>Length : 50.00 mm |   |
| CCLASPT70-3W               | Width : 15.00 mm<br>Thickness : 3.00 mm<br>Pitch : 32.00 mm<br>Length : 82.00 mm |   |
| Marker For Terminal Blocks |                                                                                  |                                                                                      |
| LABEL KN12                 | Width : 12.00 mm                                                                 |   |
| Marker carriers            |                                                                                  |                                                                                      |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                       |  |

