


## CSTD6

Terminal Type - CSTD6 , Test Disconnect Terminal Blocks , nominal voltage: 800 V, nominal current: 38 A, connection method: Screw connection, number of connections: 2, Rated cross section : 6 mm<sup>2</sup> , cross section: 1.5 mm<sup>2</sup> - 10 mm<sup>2</sup>, mounting type: TS32



### Approvals

CE

### General Information

Product Name	CSTD6
Connection Method	Screw Connection
Rating	800 V/38 A/6 mm <sup>2</sup> /0.8 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M3.5

### Dimensions & Weight

Width	8 mm	0.31 inch
Length	65 mm	2.56 inch
Height	50.1 mm	1.97 inch
Weight of std. Packing Unit	1.7 Kg	

### Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

### Rated Conductor Size

Conductor cross section flexible min	1.5 mm <sup>2</sup>
Conductor cross section flexible max	6 mm <sup>2</sup>
Conductor cross section solid min	1.5 mm <sup>2</sup>
Conductor cross section solid max	10 mm <sup>2</sup>

## Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	800 V
Nominal Current $I_n$	38 A
Nominal cross section	6 mm <sup>2</sup>
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

## Product Accessories

### DIN Rail Perforated

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---

### End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	

### End Cover

EPTD	Height : 50.00 mm Width : 2.50 mm Length : 65.00 mm	
------	---	---

<b>Insertion Bridge</b>		
ADSL-2W	Width : 20.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-10W	Width : 124.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-3W	Width : 33.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-4W	Width : 46.50 mm Pitch : 13.00 mm Length : 24.00 mm	
ADSL-7W	Width : 85.50 mm Pitch : 13.00 mm Length : 24.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.5	Width : 6.00 mm	
<b>Marker carriers</b>		
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm	
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	