


CSTM2.5

Terminal Type - CSTM2.5 , Feed Through Terminal block, nominal voltage: 800 V, nominal current: 24 A, Rated cross-section – 2.5 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 4 mm², mounting type: TS32



Approvals

CE

General Information

Product Name	CSTM2.5
Connection Method	Screw Connection
Rating	800 V/24 A/2.5 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	6 mm	0.24 inch
Length	36.5 mm	1.44 inch
Height	44 mm	1.73 inch
Weight of std. Packing Unit	1.12 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black , Green ,

Rated Conductor Size


Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC


Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---




Cover Profile Carrier









UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--




DIN Rail Perforated

CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
-----	--	---

End Clamp

SCS	Height : 26.90 mm Length : 21.00 mm	
SCSN	Height : 31.00 mm Width : 8.40 mm Length : 27.00 mm	
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPNS	Height : 31.00 mm Thickness : 1.50 mm Length : 36.50 mm	
Fixed Bridge		
CCLM2.5-2W	Height : 14.00 mm Pitch : 6.00 mm Length : 10.60 mm	
CCLM2.5-3W	Height : 14.00 mm Pitch : 6.00 mm Length : 16.60 mm	
Insertion Bridge		
SLC4N-10W	Width : 58.60 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-3W	Width : 16.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-4W	Width : 22.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-5W	Width : 28.65 mm Pitch : 6.00 mm Length : 23.00 mm	
SLC4N-6W	Width : 34.60 mm Pitch : 6.00 mm Length : 23.00 mm	

Insertion Bridge			
SLC4N-2W	Width : 10.91 mm Pitch : 6.00 mm Length : 23.00 mm		
Marker For Terminal Blocks			
LABEL KN5.5	Width : 6.00 mm		
Partition Plate			
KBXF	Height : 53.40 mm Thickness : 1.50 mm Length : 54.00 mm		
Marker carriers			
GMC	Height : 48.00 mm Width : 39.00 mm Thickness : 1.00 mm Length : 38.00 mm		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm		