



## DBP4-10WAY

Terminal Type - DBP4-10WAY , Distribution Block, nominal voltage: 500 V, nominal current: 32 A , connection method: Screw connection, number of connections: 20, cross section: 0.2 mm<sup>2</sup> - 4 mm<sup>2</sup> , mounting type: Panel mounting, surface mounting



### Approvals

CE

### General Information

Product Name	DBP4-10WAY
Connection Method	Screw Connection
Rating	500 V/32 A/4 mm <sup>2</sup> /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M3

### Dimensions & Weight

Width	74 mm	2.91 inch
Length	27 mm	1.06 inch
Height	27 mm	1.06 inch
Weight of std. Packing Unit	1.6 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

## Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	500 V
Nominal Current $I_n$	32 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.48 kA
Rated surge voltage	6 kV
Degree of pollution	3

## Product Accessories

### Marker For Terminal Blocks

LABEL KN5.5	Width : 6.00 mm	
-------------	-----------------	---

