


DMCT2.5P4

Terminal Type -DMCT2.5P4, Multi-Conductor - Mini and Micro terminal block, nominal voltage: 800 V, nominal current: 24 A, Rated cross-section - 2.5 mm², connection method: Spring clamp connection, number of connections: 4, cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15



Approvals

CE

General Information

Product Name	DMCT2.5P4
Connection Method	Spring Cage Connection
Rating	800 V/24 A/2.5 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	200
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	10 mm	0.39 inch
Length	42.2 mm	1.66 inch
Height	27.9 mm	1.1 inch
Weight of std. Packing Unit	0.96 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size


Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	NAP kA
Rated surge voltage	6 kV
Degree of pollution	3

Product Accessories


End Cover

DMEP2.5P4	Height : 21.05 mm Thickness : 2.00 mm Length : 35.60 mm	
-----------	---	---

Insertion Bridge

MSL2.5	Width : 10.30 mm Pitch : 5.95 mm Length : 15.14 mm	
--------	--	--

Marker For Terminal Blocks

LABEL KN10	Width : 10.00 mm	
------------	------------------	---