



## DPSC5.08WF-6W

Terminal Type - DPSC5.08WF - 6W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 12, cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, Rated cross-section - 2.5 mm<sup>2</sup>, mounting type: TS35/7.5 , TS35/15



### Approvals

CE

### General Information

Product Name	DPSC5.08WF-6W
Connection Method	Spring Cage Connection
Rating	250 V/16 A/2.5 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	25
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	46.37 mm	1.83 inch
Length	58.51 mm	2.3 inch
Height	26.15 mm	1.03 inch
Weight of std. Packing Unit	0.7 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size



Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

## Ratings - IEC



Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	250 V
Nominal Current $I_n$	16 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	4 kV
Degree of pollution	3

## Product Accessories

### DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

### DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

### End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

### Marker For Terminal Blocks

LABEL KN5.08	Pitch : 5.08 mm	
--------------	-----------------	---

### Tool

DPSCCOT	Height : 6.90 mm Width : 5.00 mm Length : 20.30 mm	
---------	--	---