



## DUTKD4TS

Terminal Type - DUTKD4TS , Knife Disconnect Terminal block with test socket screw , nominal voltage: 1000 V, nominal current: 20 A, connection method: Screw connection , number of connections: 2, cross section: 0.5 mm<sup>2</sup> – 4 mm<sup>2</sup>, width: 6 mm , height: 56 mm , Length : 62 mm , mounting type: TS35/7.5 , TS35/15 and TS32



### Approvals

CE

### General Information

Product Name	DUTKD4TS
Connection Method	Screw Connection
Rating	1000 V/20 A/4 mm <sup>2</sup> /0.6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	62 mm	2.44 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	1.55 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

## Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	20 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	4 kV
Degree of pollution	3

## Product Accessories

### Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

### Cover Profile Carrier

UHDD	Height : 74.50 mm Thickness : 2.00 mm Length : 55.82 mm	
------	---	--

### DIN Rail Perforated


CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

### DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

<b>End Cap</b>		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
<b>End Clamp</b>		
SCUP	Height : 34.00 mm Length : 44.75 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
<b>End Cover</b>		
DUTKD4EP	Height : 38.20 mm Width : 1.50 mm Length : 62.00 mm	
<b>Marker For Terminal Blocks</b>		
LABEL KN5.5	Width : 6.00 mm	

<b>Partition Plate</b>		
KBZF	Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm	
<b>Plug-in Bridge/Jumper</b>		
SLPU6-2W	Height : 26.00 mm Width : 10.15 mm Pitch : 6.00 mm	
SLPU6-10W	Height : 26.00 mm Width : 58.15 mm Pitch : 6.00 mm	
SLPU6-3W	Height : 26.00 mm Width : 16.15 mm Pitch : 6.00 mm	
SLPU6-4W	Height : 26.00 mm Width : 22.15 mm Pitch : 6.00 mm	
SLPU6-5W	Height : 26.00 mm Width : 28.15 mm Pitch : 6.00 mm	
SLPU6-6W	Height : 26.00 mm Width : 34.15 mm Pitch : 6.00 mm	
<b>Marker carriers</b>		
SCUDDMLH	Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 41.50 mm	
GMH 20	Height : 51.00 mm Width : 20.00 mm Length : 41.50 mm	
SCUNMLH	Height : 53.50 mm Width : 9.50 mm Length : 50.60 mm	

<b>Marker carriers</b>		
DCKNMLH	Height : 45.50 mm Width : 6.00 mm Length : 43.50 mm	
SCKNMLH	Height : 45.50 mm Width : 8.00 mm Length : 44.90 mm	