



KUF10D1

Terminal Type - KUF10D1, Fuse terminal block with LED of 24 VDC for fuse failure indication, nominal voltage: 24 V, nominal current: 12 A, Rated cross-section – 10 mm², suitable size of cartridge fuse: 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CE

General Information

| | |
|-----------------------------|--------------------------------------|
| Product Name | KUF10D1 |
| Connection Method | Screw Connection |
| Rating | 24 V/12 A/10 mm ² /1.4 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 50 |
| Country Of Origin | India |
| Screw thread | M4 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 12 mm | 0.47 inch |
| Length | 66 mm | 2.6 inch |
| Height | 63.5 mm | 2.5 inch |
| Weight of std. Packing Unit | 2.1 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Green , Khakhi , |

Rated Conductor Size

| | |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.5 mm ² |
| Conductor cross section flexible max | 10 mm ² |
| Conductor cross section solid min | 0.5 mm ² |
| Conductor cross section solid max | 10 mm ² |

Ratings - IEC



| | |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC-60947-7-1 |
| Nominal Voltage U_n | 24 V |
| Nominal Current I_n | 12 A |
| Nominal cross section | 10 mm ² |
| Short-time current | NAP kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

Product Accessories


DIN Rail Perforated

| | | |
|-------|--|---|
| CHKDS | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHKS | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |
| CHS | Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm |  |

DIN Rail, Unperforated

| | | |
|------|--|---|
| CHKD | Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm |  |
| CHK | Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm |  |

End Cap

| | | |
|-----------|---|---|
| CHKENDCAP | Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm |  |
|-----------|---|---|

End Clamp

| | | |
|------|--|---|
| SCUP | Height : 34.00 mm Length : 44.75 mm |  |
|------|--|---|

| End Clamp | | |
|-----------------------------------|--|---|
| SCUSL | Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm |  |
| SCUDD | Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm |  |
| DCKN | Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm |  |
| DCKN10 | Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm |  |
| SCKN | Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm |  |
| SCUN | Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm |  |
| End Cover | | |
| EPF | Height : 46.20 mm Width : 3.00 mm Length : 66.00 mm |  |
| Marker For Terminal Blocks | | |
| LABEL KN12 | Width : 12.00 mm |  |
| Partition Plate | | |
| KBZF | Height : 65.00 mm Width : 1.50 mm Length : 65.00 mm |  |
| Marker carriers | | |
| SCUDDMLH | Height : 71.50 mm Width : 10.00 mm Length : 55.60 mm |  |