


CBTM5

Terminal Type - CBTM5 , Feed Through Terminal Block , nominal voltage: 800 V, nominal current: 76 A, connection method: Bolt Connection - Nut driver operated , number of connections: 2, cross section: 2.5 mm² - 16 mm², width: 15 mm , length: 46 mm , height : 42 mm , mounting type :TS32 , colour :KHAKHI



Approvals

CE

General Information

Product Name	CBTM5
Connection Method	Bolt Connection
Rating	800 V/76 A/16 mm ² /2 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	M5

Dimensions & Weight

Width	15 mm	0.59 inch
Length	46 mm	1.81 inch
Height	42 mm	1.65 inch
Weight of std. Packing Unit	1.54 Kg	

Material Data

Insulating Material	Melamine
Standard Colour	Khakhi
Colour Variants	Red , Yellow , Blue , Black ,

Rated Conductor Size

Conductor cross section flexible min	2.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	2.5 mm ²
Conductor cross section solid max	16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60974-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	76 A
Nominal cross section	16 mm ²
Short-time current	1.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

