


DBK150/M6C-1X4

Terminal Type - DBK150/M6C-1X4 , Distribution Block, nominal voltage: 800 V, nominal current: IC-309 A , OG-101 A ,Rated cross-section- IC-150 mm², OG-25 mm², connection method: Bolt connection, number of connections: 9 , cross-section: IC- 70 - 150 mm² , OG -6-25 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CE

General Information

| | |
|-----------------------------|---|
| Product Name | DBK150/M6C-1X4 |
| Connection Method | Bolt Connection |
| Rating | 800 V/IC-309 A, OG-101 A/IC-150 mm ² , OG-25 mm ² /IC-14 Nm , OG-2.5 Nm |
| HSN Number | 85389000 |
| Standard Packing Qty(in No) | 5 |
| Country Of Origin | India |
| Screw thread | IC-M12 , OG-M6 |

Dimensions & Weight

| | | |
|-----------------------------|---------|-----------|
| Width | 109 mm | 4.29 inch |
| Length | 84.3 mm | 3.32 inch |
| Height | 58.2 mm | 2.29 inch |
| Weight of std. Packing Unit | 1.6 Kg | |

Material Data

| | |
|---------------------|--|
| Insulating Material | Polyamide 6,6 |
| Standard Colour | Gray |
| Colour Variants | Red , Yellow , Blue , Black , Green , Khakhi , |

Rated Conductor Size

| | |
|--------------------------------------|--|
| Conductor cross section flexible min | IC-50 mm ² , OG-6 mm ² |
| Conductor cross section flexible max | IC-150 mm ² , OG-25 mm ² |
| Conductor cross section solid min | IC-50 mm ² , OG-6 mm ² |
| Conductor cross section solid max | IC-150 mm ² , OG-25 mm ² |

Ratings - IEC

| | |
|----------------------------------|--|
| Connection in acc. with standard | IEC 60947-7-1 |
| Nominal Voltage U_n | 800 V |
| Nominal Current I_n | IC-309 A, OG-101 A |
| Nominal cross section | IC-150 mm ² , OG-25 mm ² |
| Short-time current | 18 kA |
| Rated surge voltage | 8 kV |
| Degree of pollution | 3 |

