



## DPSC5.08PM-3W

Terminal Type - DPSC5.08PM - 3W , Plug & socket type terminal block , nominal voltage: 250 V, nominal current: 16 A, connection method: Spring cage connection , number of connections: 6, cross section: 0.2 mm<sup>2</sup> - 2.5 mm<sup>2</sup>, Rated cross section: 2.5 mm<sup>2</sup>, mounting type: Panel mounting / Surface mounting



### Approvals

CE

### General Information

Product Name	DPSC5.08PM-3W
Connection Method	Spring Cage Connection
Rating	250 V/16 A/2.5 mm <sup>2</sup> / Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAV

### Dimensions & Weight

Width	31.13 mm	1.23 inch
Length	45.25 mm	1.78 inch
Height	14.45 mm	0.57 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.2 mm <sup>2</sup>
Conductor cross section flexible max	2.5 mm <sup>2</sup>
Conductor cross section solid min	0.2 mm <sup>2</sup>
Conductor cross section solid max	2.5 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	250 V
Nominal Current $I_n$	16 A
Nominal cross section	2.5 mm <sup>2</sup>
Short-time current	0.18 kA
Rated surge voltage	4 kV
Degree of pollution	3

