



## DUTKD4

Terminal Type - DUTKD4 , Knife Disconnect Terminal block , nominal voltage: 1000 V, nominal current: 20 A, Rated Cross -Section : 4 mm<sup>2</sup> , connection method: Screw connection, number of connections: 2, cross section: 0.5 mm<sup>2</sup> – 4 mm<sup>2</sup> , mounting type: TS35/7.5 , TS35/15 and TS32



### Approvals

CE

### General Information

Product Name	DUTKD4
Connection Method	Screw Connection
Rating	1000 V/20 A/4 mm <sup>2</sup> /0.6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M2.6

### Dimensions & Weight

Width	6 mm	0.24 inch
Length	62 mm	2.44 inch
Height	56 mm	2.2 inch
Weight of std. Packing Unit	1.44 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	0.5 mm <sup>2</sup>
Conductor cross section flexible max	4 mm <sup>2</sup>
Conductor cross section solid min	0.5 mm <sup>2</sup>
Conductor cross section solid max	4 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	20 A
Nominal cross section	4 mm <sup>2</sup>
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

