


KUDF4

Terminal Type - KUDF4 , Fuse terminal block, nominal voltage: 800 V, nominal current: 6.3 A , suitable size of cartridge fuse : 5X20 mm and 5X25 mm , connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 4 mm², AWG: 20 - 12, width: 8 mm , length: 54.5 mm , height : 44 mm , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals

CE

General Information

Product Name	KUDF4
Connection Method	Screw Connection
Rating	800 V/6.3 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	8 mm	0.31 inch
Length	54.5 mm	2.15 inch
Height	44 mm	1.73 inch
Weight of std. Packing Unit	1.49 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-3
Nominal Voltage U_n	800 V
Nominal Current I_n	6.3 A
Nominal cross section	4 mm ²
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

