



KUFH4A2

Terminal Type - KUFH4A2 , Fuse terminal block with LED for 110 VAC , nominal voltage: 110 V, nominal current: 12 A , suitable size of cartridge fuse : 6.35X32 mm , connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 6 mm², AWG: 24 -10, width: 9 mm , length: 77.7 mm , height : 53.5 mm , mounting type: TS 35/7.5 , TS 35/15 , TS 32



Approvals

CE

General Information

Product Name	KUFH4A2
Connection Method	Screw Connection
Rating	110 V/12 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	9 mm	0.35 inch
Length	77.7 mm	3.06 inch
Height	53.5 mm	2.11 inch
Weight of std. Packing Unit	1.9 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC-60947-7-3
Nominal Voltage U_n	110 V
Nominal Current I_n	12 A
Nominal cross section	4 mm ²
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

