


KUT50A

Terminal Type - KUT50A , Feed-through terminal block, Nominal voltage: 1000 V, Nominal current: 150 A, Connection method: Screw connection, Operated by: 5mm Allen Key, Number of connections: 2, cross section: 16 mm² - 50 mm², AWG: 2/0-6, width: 20.5 mm , length : 71 mm , height : 75.5 mm , mounting type: TS35/7.5 , TS35/15 , and TS32



Approvals

General Information

Product Name	KUT50A
Connection Method	Screw Connection
Rating	1000 V/150 A/50 mm ² /3 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M6

Dimensions & Weight

Width	20.5 mm	0.81 inch
Length	71 mm	2.8 inch
Height	75.5 mm	2.97 inch
Weight of std. Packing Unit	1.24 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	16 mm ²
Conductor cross section flexible max	50 mm ²
Conductor cross section solid min	16 mm ²
Conductor cross section solid max	70 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	150 A
Nominal cross section	50 mm ²
Short-time current	6 kA
Rated surge voltage	12 kV
Degree of pollution	3

