


SPT240XL

Terminal Type - SPT240XL , High current connectors with secured hinged cover , nominal voltage: 1000 V, nominal current: 415 A, connection method: Bolt connection , Bolt with clinched conical , number of connections: 2, cross section: 25 mm² - 240 mm² , width: 55 mm , length: 286.8 mm , height : 89.3 mm , mounting type: TS 35/7.5 and TS 35/15



Approvals

CE

General Information

Product Name	SPT240XL
Connection Method	Bolt Connection
Rating	1000 V/415 A/240 mm ² /14 Nm
HSN Number	85389000
Standard Packing Qty(in No)	5
Country Of Origin	India
Screw thread	M12

Dimensions & Weight

Width	55 mm	2.17 inch
Length	286.8 mm	11.29 inch
Height	89.3 mm	3.52 inch
Weight of std. Packing Unit	2.71 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	25 mm ²
Conductor cross section flexible max	240 mm ²
Conductor cross section solid min	25 mm ²
Conductor cross section solid max	240 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	415 A
Nominal cross section	240 mm ²
Short-time current	28.80 kA
Rated surge voltage	8 kV
Degree of pollution	3

