


## SPT95XL

Terminal Type - SPT95XL , High current connectors with secured hinged cover , nominal voltage: 1000 V, nominal current: 232 A, connection method: Bolt connection, Bolt with clinched conical , number of connections: 2, cross section: 16 mm<sup>2</sup> - 95 mm<sup>2</sup> , width: 32 mm , length: 180 mm , height : 71 mm , mounting type: TS 35/7.5 and TS 35/15



### Approvals

CE

### General Information

Product Name	SPT95XL
Connection Method	Bolt Connection
Rating	1000 V/232 A/95 mm <sup>2</sup> /6 Nm
HSN Number	85389000
Standard Packing Qty(in No)	10
Country Of Origin	India
Screw thread	M8

### Dimensions & Weight

Width	32 mm	1.26 inch
Length	180 mm	7.09 inch
Height	71 mm	2.8 inch
Weight of std. Packing Unit	0 Kg	

### Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

### Rated Conductor Size

Conductor cross section flexible min	16 mm <sup>2</sup>
Conductor cross section flexible max	95 mm <sup>2</sup>
Conductor cross section solid min	16 mm <sup>2</sup>
Conductor cross section solid max	95 mm <sup>2</sup>

**Ratings - IEC**

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage $U_n$	1000 V
Nominal Current $I_n$	232 A
Nominal cross section	95 mm <sup>2</sup>
Short-time current	11.4 kA
Rated surge voltage	8 kV
Degree of pollution	3

