



UBDF4A1

Terminal Type - UBDF4A1, Fuse terminal block with LED for 110 VAC, nominal voltage: 110 V, Rated cross-section - 4 mm², nominal current: 6.3 A, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 6 mm², AWG: 24 -10, mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CE

General Information

Product Name	UBDF4A1
Connection Method	Screw Connection
Rating	110 V/6.3 A/4 mm ² /0.5 Nm
HSN Number	85389000
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	8.25 mm	0.32 inch
Length	72.5 mm	2.85 inch
Height	56.5 mm	2.22 inch
Weight of std. Packing Unit	1.9 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC-60947-7-3
Nominal Voltage U_n	110 V
Nominal Current I_n	6.3 A
Nominal cross section	4 mm ²
Short-time current	0 kA
Rated surge voltage	8 kV
Degree of pollution	3

