

KU2D4

Terminal Type - KU2D4, Multi level terminal block, nominal voltage: 500 V, nominal current: 24 A, connection method: Screw connection, number of connections: 4, Rated cross section - 2.5 mm², cross-section: 0.5 mm² - 4 mm², AWG: 20 - 12, mounting type: TS 35/7.5, TS 35/15, TS 32

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier









UHDD	Height : 74.50 mm Width : 2.00 mm Length : 55.82 mm	
------	---	---




DIN Rail Perforated







CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
EPDD4	Height : 41.00 mm Width : 1.50 mm Length : 50.00 mm	

Fixed Bridge		
CCLADD-2W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 11.30 mm	
CCLADD-10W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 59.30 mm	
CCLADD-3W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 17.30 mm	
CCLADD-4W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 23.30 mm	
CCLADD-5W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 29.30 mm	
CCLADD-6W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 35.30 mm	
CCLADD-7W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 41.30 mm	
CCLADD-8W	Height : 16.50 mm Width : 5.40 mm Pitch : 6.00 mm Length : 47.30 mm	
Insertion Bridge		
SLC4N-10W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 58.60 mm	
SLC4N-3W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 16.65 mm	
SLC4N-4W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 22.65 mm	

Insertion Bridge			
SLC4N-5W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 28.65 mm		
SLC4N-6W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 34.65 mm		
SLC4N-2W	Height : 23.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 10.91 mm		
Marker For Terminal Blocks			
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm		
Marker carriers			
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm		
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm		
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm		