










## SPT120

Terminal Type – SPT120, High current connectors with secured hinged cover, nominal voltage: 1000 V AC/1500 V DC, nominal current: 269 A, Rated cross-section – 120 mm<sup>2</sup>, connection method: Bolt connection, number of connections: 2, cross-section: 10mm<sup>2</sup> - 120 mm<sup>2</sup>, 10AWG - 300 KCMIL, mounting type: TS 35/7.5, TS 35/15

### Product Accessories

| DIN Rail Perforated    |                                                                                      |                                                                                       |
|------------------------|--------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CHKDS                  | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm<br>Length : 2,000.00 mm |    |
| CHKS                   | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |    |
| DIN Rail, Unperforated |                                                                                      |                                                                                       |
| CHKD                   | Height : 15.00 mm<br>Width : 35.00 mm<br>Thickness : 1.50 mm                         |   |
| CHK                    | Height : 7.50 mm<br>Width : 35.00 mm<br>Thickness : 1.00 mm                          |  |
| End Cap                |                                                                                      |                                                                                       |
| CHKENDCAP              | Height : 14.00 mm<br>Width : 9.00 mm<br>Length : 41.50 mm                            |  |
| End Clamp              |                                                                                      |                                                                                       |
| SCUP                   | Height : 34.00 mm<br>Width : 9.00 mm<br>Length : 44.75 mm                            |  |
| SCUDD                  | Height : 50.00 mm<br>Width : 10.00 mm<br>Length : 55.60 mm                           |  |
| SCUSL                  | Height : 41.10 mm<br>Width : 8.00 mm<br>Length : 47.50 mm                            |  |

| Fixed Bridge               |                                                                                  |                                                                                       |
|----------------------------|----------------------------------------------------------------------------------|---------------------------------------------------------------------------------------|
| CCLASPT150-2W              | Width : 18.00 mm<br>Thickness : 3.00 mm<br>Pitch : 42.00 mm<br>Length : 68.00 mm |    |
| CCLASPT150-3W              | Width : 18.00 mm<br>Thickness : 3.00 mm<br>Pitch : 42.00 mm<br>Length : 68.00 mm |    |
| Marker For Terminal Blocks |                                                                                  |                                                                                       |
| LABEL KN12                 | Height : 2.43 mm<br>Width : 12.00 mm<br>Length : 8.50 mm                         |    |
| Marker carriers            |                                                                                  |                                                                                       |
| SCUDDMLH                   | Height : 71.50 mm<br>Width : 11.00 mm<br>Length : 55.60 mm                       |   |
| GMH20                      | Height : 51.00 mm<br>Width : 20.00 mm<br>Length : 42.25 mm                       |  |
| GMH10                      | Height : 51.00 mm<br>Width : 10.00 mm<br>Length : 42.25 mm                       |  |
| SCKNMLH                    | Height : 42.00 mm<br>Width : 16.00 mm<br>Length : 44.70 mm                       |  |