



SUT10

Terminal Type - SUT10, Mini and Micro feed through terminal block, nominal voltage: 500 V, nominal current: 57 A, Rated cross-section - 10 mm², connection method: Screw connection, number of connections: 2, cross-section: 0.2 mm² - 10 mm², AWG: 24 - 8, mounting type: TS15

Product Accessories

DIN Rail Perforated		
CHM	Height : 5.00 mm Width : 15.00 mm Thickness : 1.00 mm	
End Clamp		
SCMN	Height : 18.00 mm Width : 6.10 mm Length : 23.50 mm	
Marker For Terminal Blocks		
LABEL KN10	Height : 2.89 mm Width : 10.00 mm Length : 8.50 mm	
Partition Plate		
MBX	Height : 36.70 mm Width : 1.50 mm Length : 43.50 mm	
Plug-in Bridge/Jumper		
MLPU10-2W	Height : 23.17 mm Width : 2.75 mm Pitch : 10.00 mm Length : 17.50 mm	
MLPU10-3W	Height : 23.17 mm Width : 2.75 mm Pitch : 10.00 mm Length : 27.50 mm	
MLPU10-4W	Height : 23.17 mm Width : 2.75 mm Pitch : 10.00 mm Length : 37.50 mm	
MLPU10-5W	Height : 23.17 mm Width : 2.75 mm Pitch : 10.00 mm Length : 47.50 mm	