



KUT4NTC-K

Terminal Type - KUT4NTC-K, Thermocouple terminal block, ' K Type - Chromel (Ni/Cr)Alumel (Ni/Al) , nominal voltage: 400 V, nominal current: 5 A, connection method: Screw connection, number of connections: 4, Rated cross section : 4 mm², cross section: 0.5 mm² - 4 mm², mounting type: TS35/7.5, TS35/15, TS32



Approvals



General Information

Product Name	KUT4NTC-K
Connection Method	Screw Connection
Rating	400 V / 5 A / 4 mm ² / 0.5 Nm
HSN Number	8904476702227
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	12 mm	0.47 inch
Length	44.25 mm	1.74 inch
Height	51 mm	2.01 inch
Weight of std. Packing Unit	1.34 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²


Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	4 mm ²

Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	4 mm ²

Product Accessories


Cover Profile

PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---

Cover Profile Carrier

UHDD	Height : 74.50 mm Width : 2.00 mm Length : 55.82 mm	
------	---	---


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	


DIN Rail, Unperforated








CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	



End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
------	---	---

End Clamp		
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
KPXN	Height : 41.50 mm Width : 1.50 mm Length : 41.50 mm	
Partition Plate		
KNBF 2.5/10	Height : 58.00 mm Width : 1.50 mm Length : 55.50 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	

Marker carriers			
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm		
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm		
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm		

