


OAT10DTS

Terminal Type - OAT10DTS, Test Disconnect terminal block, nominal voltage: 1000 V, nominal current: 57 A, Rated cross-section - 10 mm² connection method: Bolt connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals

CB LRCE

General Information

Product Name	OAT10DTS
Connection Method	Bolt Connection
Rating	1000 V / 57 A / 10 mm ² / 2 Nm
HSN Number	8904476704191
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	13 mm	0.51 inch
Length	95 mm	3.74 inch
Height	63.45 mm	2.5 inch
Weight of std. Packing Unit	3.5 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²



Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	




DIN Rail, Unperforated






CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	


End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---




End Clamp

SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	

End Clamp		
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP10DTS	Height : 43.50 mm Width : 2.00 mm Length : 95.00 mm	
Insertion Bridge		
OSL10R(4+1)AW	Height : 29.40 mm Pitch : 13.00 mm Length : 101.00 mm	
Marker For Terminal Blocks		
LABEL KN12	Height : 2.43 mm Width : 12.00 mm Length : 8.50 mm	
Partition Plate		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
Switching Jumper		
OSLD10-2W	Height : 27.50 mm Width : 23.50 mm Pitch : 13.00 mm	

Switching Jumper			
OSLD10-3W	Height : 27.50 mm Width : 36.50 mm Pitch : 13.00 mm		
OSLD10-4W	Height : 27.50 mm Width : 49.50 mm Pitch : 13.00 mm		

Test Adapter / Test Socket			
OAT6DTSTP-B	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-BL	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-G	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-GR	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-R	Height : 41.70 mm Width : 6.00 mm		
OAT6DTSTP-Y	Height : 41.00 mm Width : 6.00 mm		

Marker carriers			
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm		
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm		

Marker carriers			
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm		

