


OAT6

Terminal Type - OAT6, Feed through terminal block with secured hinged cover, nominal voltage: 1000 V, nominal current: 57 A, Rated Cross-Section : 10 mm², connection method: Bolt connection, number of connections: 2, cross section: 1.5 mm² - 10 mm², AWG: 20 - 10 , mounting type: TS 35/7.5, TS 35/15 , TS 32



Approvals



General Information

Product Name	OAT6
Connection Method	Bolt Connection
Rating	1000 V / 57 A / 10 mm ² / 1.5 Nm
HSN Number	8904476704160
Standard Packing Qty (in No)	100
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	11 mm	0.43 inch
Length	44.5 mm	1.75 inch
Height	51 mm	2.01 inch
Weight of std. Packing Unit	2.41 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	10 mm ²

Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U _N	630 V
ATEX Nominal Current I _N	28 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - CSA


CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U _N	600 V
B - CSA Nominal Current I _N	30 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	10 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	30 A
B - UL Wire Min	20 AWG
B - UL Wire Max	10 AWG

Product Accessories

Cover Profile








PCK3	Height : 28.00 mm Width : 58.35 mm Thickness : 1.00 mm	
------	--	---





Cover Profile Carrier





UHDD	Height : 74.50 mm Width : 2.00 mm Length : 55.82 mm	
------	---	---

DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail Perforated		
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	
DIN Rail, Unperforated		
CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	

End Clamp		
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
OEP 6	Height : 39.50 mm Width : 1.50 mm Length : 43.50 mm	
Insertion Bridge		
OSL6-10W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6-2W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 19.00 mm	
OSL6-3W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 30.00 mm	
OSL6-4W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 41.00 mm	
OSL6-5W	Height : 25.50 mm Width : 3.50 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6R-10W	Height : 25.70 mm Pitch : 11.00 mm Length : 107.00 mm	
OSL6R-2W	Height : 25.70 mm Pitch : 11.00 mm Length : 19.00 mm	
OSL6R-3W	Height : 25.70 mm Pitch : 11.00 mm Length : 30.00 mm	

Insertion Bridge		
OSL6R-4W	Height : 25.70 mm Pitch : 11.00 mm Length : 41.00 mm	
OSL6R-5W	Height : 25.70 mm Pitch : 11.00 mm Length : 52.00 mm	
OSL6R-6W	Height : 25.70 mm Pitch : 11.00 mm Length : 63.00 mm	
Marker For Terminal Blocks		
LABEL KN 9	Height : 2.00 mm Width : 9.00 mm Length : 6.00 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	