


ONTM5-16C

Terminal Type - ONTM5-16C, Feed Through Terminal Block, nominal voltage: 1000 V, nominal current: 76 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2 , Rated Cross-section : 16 mm², cross section: 1.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	ONTM5-16C
Connection Method	Bolt Connection
Rating	1000 V / 76 A / 16 mm ² / 2 Nm
HSN Number	8904476704238
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	13 mm	0.51 inch
Length	48 mm	1.89 inch
Height	36.5 mm	1.44 inch
Weight of std. Packing Unit	1.35 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	16 mm ²

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	16 mm ²



Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	16 mm ²

Product Accessories


DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	
CHS	Height : 15.00 mm Width : 32.00 mm Thickness : 1.50 mm	




DIN Rail, Unperforated









CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	




End Cap

CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
-----------	---	---

End Clamp

SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	

End Clamp		
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
ONTEP	Height : 22.80 mm Width : 2.00 mm Length : 47.80 mm	
Fixed Bridge		
CCLAONT13-2W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 17.80 mm	
CCLAONT13-10W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 121.80 mm	
CCLAONT13-3W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 30.80 mm	
CCLAONT13-4W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 43.80 mm	
CCLAONT13-5W	Height : 18.30 mm Width : 4.80 mm Pitch : 13.00 mm Length : 56.80 mm	

Marker For Terminal Blocks		
ONTML13	Height : 2.42 mm Width : 13.00 mm Length : 11.50 mm	
Partition Plate		
KBXF	Height : 53.40 mm Width : 1.50 mm Length : 54.00 mm	
Marker carriers		
GMH20	Height : 51.00 mm Width : 20.00 mm Length : 42.25 mm	
GMH10	Height : 51.00 mm Width : 10.00 mm Length : 42.25 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	