


PQT2.5

Terminal Type - PQT2.5, PCB Connector, nominal voltage: 500 V, nominal current: 15 A, connection method: Pushing connection, number of connections: 1 , cross-section: 0.5 mm² - 2.5 mm², AWG: 24 - 12, mounting type - Printed circuit board (PCB)



Approvals



General Information

Product Name	PQT2.5
Connection Method	Push In Connection
Rating	500 V / 15 A / 2.5 mm ² / NAV Nm
HSN Number	8904476700971
Standard Packing Qty (in No)	250
Country Of Origin	India
Screw thread	NA

Dimensions & Weight

Width	7.5 mm	0.3 inch
Length	19 mm	0.75 inch
Height	23.7 mm	0.93 inch
Weight of std. Packing Unit	1.08 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	-

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²

Conductor cross section solid max	2.5 mm ²
-----------------------------------	---------------------

Product Accessories

Marker For Terminal Blocks		
LABEL KN7.5	Height : 1.60 mm Pitch : 7.50 mm Length : 3.40 mm	