



SQ4-2T

Terminal Type - SQ4-2T, Multi level Feed Through terminal block, connection method: Spring cage connection, Nominal Voltage : 1000 V, nominal Current : 32 A , number of connections: 4, cross section: 0.08 mm² - 6 mm², AWG 24-10, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	SQ4-2T
Connection Method	Spring Cage Connection
Rating	1000 V / 32 A / 4 mm ²
HSN Number	8904476701176
Standard Packing Qty (in No)	100
Country Of Origin	INDIA
Screw thread	-

Dimensions & Weight

Width	6 mm	0.24 inch
Length	88.1 mm	3.47 inch
Height	47 mm	1.85 inch
Weight of std. Packing Unit	1.7 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	4 mm ²

Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	6 mm ²

Ratings - ATEX


ATEX Standard	EN 60049-7
ATEX Nominal Voltage U _N	630 V
ATEX Nominal Current I _N	26 A
ATEX Cross Sec. Flexible Max.	4 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	600 V
B - UL Nominal Current I _N	30 A
B - UL Wire Min	24 AWG
B - UL Wire Max	10 AWG

Product Accessories

Cover Profile










PCPDBF-5	Height : 14.10 mm Thickness : 1.50 mm Length : 113.00 mm	
----------	--	---


DIN Rail Perforated



CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
End Cover		
CSP4-2T	Height : 33.40 mm Width : 2.00 mm Length : 87.80 mm	

Marker For Terminal Blocks		
LABEL KN5.5	Height : 2.42 mm Width : 6.00 mm Length : 7.50 mm	
Partition Plate		
DBF-5	Height : 54.00 mm Width : 3.00 mm Length : 112.00 mm	
Plug-in Bridge/Jumper		
SLPU6-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 10.15 mm	
SLPU6-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 58.15 mm	
SLPU6-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 16.15 mm	
SLPU6-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 22.15 mm	
SLPU6-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 28.15 mm	
SLPU6-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 6.00 mm Length : 34.15 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
DSDDM2.5MLH	Height : 24.10 mm Width : 5.00 mm Length : 19.70 mm	

Marker carriers		
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	

