



TQK6

Terminal Type - TQK6, Knife Disconnect Terminal block, nominal voltage: 1000 V, nominal current: 22 A, Rated cross-section – 6.0 mm², connection method: Screw connection, number of connections: 2, Rated cross-section: 0.2 mm² – 10 mm², mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	TQK6
Connection Method	Screw Connection
Rating	1000 V / 22 A / 6 mm ² / 0.8 Nm
HSN Number	8904476701923
Standard Packing Qty (in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	58.5 mm	2.3 inch
Height	49.5 mm	1.95 inch
Weight of std. Packing Unit	0.95 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red, Yellow, Blue, Black, Green, Khakhi

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²

Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Ratings - ATEX


ATEX Standard	EN 60049-7
ATEX Nominal Voltage U _N	630 V
ATEX Nominal Current I _N	20 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U _N	300 V
B - UL Nominal Current I _N	20 A
B - UL Wire Min	24 AWG
B - UL Wire Max	8 AWG

Product Accessories

Cover Profile








PCPDBF-3	Height : 14.10 mm Thickness : 1.50 mm Length : 79.00 mm	
----------	---	---



DIN Rail Perforated

CHKDS	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm Length : 2,000.00 mm	
CHKS	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

DIN Rail, Unperforated

CHKD	Height : 15.00 mm Width : 35.00 mm Thickness : 1.50 mm	
CHK	Height : 7.50 mm Width : 35.00 mm Thickness : 1.00 mm	

End Cap		
CHKENDCAP	Height : 14.00 mm Width : 9.00 mm Length : 41.50 mm	
End Clamp		
SCUP	Height : 34.00 mm Width : 9.00 mm Length : 44.75 mm	
SCEC35	Height : 31.50 mm Width : 8.00 mm Length : 45.80 mm	
SCUSL	Height : 41.10 mm Width : 8.00 mm Length : 47.50 mm	
SCUDD	Height : 50.00 mm Width : 10.00 mm Length : 55.60 mm	
DCKN	Height : 33.00 mm Width : 6.00 mm Length : 43.50 mm	
DCKN10	Height : 35.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKN	Height : 34.50 mm Width : 8.00 mm Length : 44.90 mm	
SCUN	Height : 35.50 mm Width : 9.50 mm Length : 50.60 mm	
Marker For Terminal Blocks		
LABEL KN8	Height : 2.43 mm Width : 8.00 mm Length : 8.50 mm	

Partition Plate		
DBF-3	Height : 50.00 mm Width : 3.00 mm Length : 78.00 mm	
Plug-in Bridge/Jumper		
MLPU8-10W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 79.20 mm	
MLPU8-2W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 15.20 mm	
MLPU8-3W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 23.20 mm	
MLPU8-4W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 31.20 mm	
MLPU8-5W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 39.20 mm	
MLPU8-6W	Height : 26.00 mm Width : 3.00 mm Pitch : 8.00 mm Length : 47.20 mm	
Marker carriers		
SCUDDMLH	Height : 71.50 mm Width : 11.00 mm Length : 55.60 mm	
SCUNMLH	Height : 53.50 mm Width : 11.00 mm Length : 50.60 mm	
DCKNMLH	Height : 45.00 mm Width : 10.00 mm Length : 43.50 mm	
SCKNMLH	Height : 42.00 mm Width : 16.00 mm Length : 44.70 mm	