



DS3L2.5

Terminal Type - DS3L2.5 , Multi-level terminal block, nominal voltage: 500 V, nominal current: 20 A, Rated cross-section – 2.5 mm², connection method: Spring Cage connection, number of connections: 6, cross-section: 0.5 mm² - 2.5 mm², AWG : 22-14 , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	DS3L2.5
Connection Method	Spring Cage Connection
Rating	500 V/20 A/2.5 mm ² /NAP Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	6 mm	0.24 inch
Length	113 mm	4.45 inch
Height	64.5 mm	2.54 inch
Weight of std. Packing Unit	1.23 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	500 V
Nominal Current I_n	20 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	
ATEX Nominal Voltage U_n	V
ATEX Nominal Current I_n	A
ATEX Cross Sec. Flexible Max.	mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	300 V
B - CSA Nominal Current I_N	15 A
B - CSA Wire Min	22 AWG
B - CSA Wire Max	14 AWG

Ratings - UL

UL Standard	
B - UL Nominal Voltage U_N	0 V
B - UL Nominal Current I_N	0 A
B - UL Wire Min	AWG
B - UL Wire Max	AWG