



KUDD4MOV

Terminal Type - KUDD4MOV, Component Housings terminal block, With MOVs - GE 14 , V275, connection method: Screw connection, number of connections: 4, Rated cross section - 2.5 mm², cross-section: 0.5 mm² - 2.5 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KUDD4MOV
Connection Method	Screw Connection
Rating	NAV V/NAV A/2.5 mm ² /0.4 Nm
HSN Number	8904476704344
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	9 mm	0.35 inch
Length	54 mm	2.13 inch
Height	59.7 mm	2.35 inch
Weight of std. Packing Unit	1.49 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi , Gray ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	NAV V
Nominal Current I_n	NAV A
Nominal cross section	2.5 mm ²
Short-time current	0 kA
Rated surge voltage	6 kV
Degree of pollution	3

