



KUF10A1

Terminal Type - KUF10A1, Fuse terminal block with LED of 110 VAC for fuse failure indication, nominal voltage: 110 V, nominal current: 12 A ,Rated cross-section – 10 mm², suitable size of cartridge fuse: 5X20 mm and 5X25 mm, connection method: Screw connection, number of connections: 2, cross-section: 0.5 mm² - 10 mm², AWG: 18 - 6, mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KUF10A1
Connection Method	Screw Connection
Rating	110 V/12 A/10 mm ² /1.4 Nm
HSN Number	8904476704795
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M4

Dimensions & Weight

Width	12 mm	0.47 inch
Length	66 mm	2.6 inch
Height	64.25 mm	2.53 inch
Weight of std. Packing Unit	2.1 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	10 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC-60947-7-1
Nominal Voltage U_n	110 V
Nominal Current I_n	12 A
Nominal cross section	10 mm ²
Short-time current	NAP kA
Rated surge voltage	8 kV
Degree of pollution	3

