


KULTD6FT

Terminal Type - KULTD6FT , Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 41 A , connection method: Screw connection with spring support , number of connections: 2, cross section: 0.5 mm² - 10 mm² , AWG: 24-8, mounting type: TS 35/7.5, TS 35/15, and TS 32



Approvals



General Information

Product Name	KULTD6FT
Connection Method	Screw Connection with spring support
Rating	1000 V/41 A/6 mm ² /1 Nm
HSN Number	85389000
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	85.2 mm	3.35 inch
Height	71.5 mm	2.81 inch
Weight of std. Packing Unit	1.98 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

