


KUTSD6

Terminal Type - KUTSD6, Disconnecting terminal block, nominal voltage: 800 V, nominal current: 41 A, Rated cross-section- 6 mm², connection method: Screw connection, number of connections: 2, cross section: 0.5 mm² - 10 mm², AWG: 20-8 , mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	KUTSD6
Connection Method	Screw Connection
Rating	800 V/41 A/6 mm ² /1.4 Nm
HSN Number	8904476702272
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M3.5

Dimensions & Weight

Width	8 mm	0.31 inch
Length	65 mm	2.56 inch
Height	46.75 mm	1.84 inch
Weight of std. Packing Unit	1.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Orange , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	800 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	400 V
ATEX Nominal Current I_n	35 A
ATEX Cross Sec. Flexible Max.	6 mm ²

Ratings - CSA

CSA Standard	CSA C22.2 NO 158
B - CSA Nominal Voltage U_N	600 V
B - CSA Nominal Current I_N	35 A
B - CSA Wire Min	20 AWG
B - CSA Wire Max	8 AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	35 A
B - UL Wire Min	20 AWG
B - UL Wire Max	8 AWG