


ONTM3-6C

Terminal Type - ONTM3-6C, Feed Through Terminal Block , nominal voltage: 1000 V, nominal current: 41 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2, Rated Cross-section : 6 mm², cross section: 0.5 mm² - 6 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	ONTM3-6C
Connection Method	Bolt Connection
Rating	1000 V/41 A/6 mm ² /0.5 Nm
HSN Number	8904476704221
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	M3

Dimensions & Weight

Width	9 mm	0.35 inch
Length	48 mm	1.89 inch
Height	36.5 mm	1.44 inch
Weight of std. Packing Unit	1.3 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.5 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.5 mm ²
Conductor cross section solid max	6 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

