


ONTM5-16C

Terminal Type - ONTM5-16C, Feed Through Terminal Block, nominal voltage: 1000 V, nominal current: 76 A, connection method : Bolt Connection - Screw and Nut driver operated, number of connections: 2 , Rated Cross-section : 16 mm², cross section: 1.5 mm² - 16 mm², mounting type: TS 35/7.5, TS 35/15, TS 32



Approvals



General Information

Product Name	ONTM5-16C
Connection Method	Bolt Connection
Rating	1000 V/76 A/16 mm ² /2 Nm
HSN Number	8904476704238
Standard Packing Qty(in No)	50
Country Of Origin	India
Screw thread	M5

Dimensions & Weight

Width	13 mm	0.51 inch
Length	48 mm	1.89 inch
Height	36.5 mm	1.44 inch
Weight of std. Packing Unit	1.35 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	1.5 mm ²
Conductor cross section flexible max	16 mm ²
Conductor cross section solid min	1.5 mm ²
Conductor cross section solid max	16 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	76 A
Nominal cross section	16 mm ²
Short-time current	1.92 kA
Rated surge voltage	8 kV
Degree of pollution	3

