



PGQ1.5

Terminal Type – PGQ 1.5, Ground modular terminal block , connection method: push in connection , number of connections: 2, cross section: 0.08 mm² – 2.5 mm² , mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PGQ1.5
Connection Method	Push In Connection
Rating	NAP V/NAP A/1.5 mm ² /NAP Nm
HSN Number	8904476700865
Standard Packing Qty(in No)	100
Country Of Origin	INDIA
Screw thread	NAP

Dimensions & Weight

Width	3.5 mm	0.14 inch
Length	47.56 mm	1.87 inch
Height	30.7 mm	1.21 inch
Weight of std. Packing Unit	0.4 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Green-Yellow
Colour Variants	

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	1.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-2
Nominal Voltage U_n	NAP V
Nominal Current I_n	NAP A
Nominal cross section	1.5 mm ²
Short-time current	0.18 kA
Rated surge voltage	0 kV
Degree of pollution	3

