


PQ1.5

Terminal Type - PQ1.5, Feed-through terminal block, nominal voltage: 1000 V, nominal current: 17.5 A, Rated cross-section - 1.5 mm², connection method: Push-in connection, number of connections: 2, cross-section: 0.2 mm² - 2.5 mm², AWG: 24- 14, mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	PQ1.5
Connection Method	Push In Connection
Rating	1000 V/17.5 A/1.5 mm ² /NAP Nm
HSN Number	8904476700636
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	3.5 mm	0.14 inch
Length	47.2 mm	1.86 inch
Height	30.5 mm	1.2 inch
Weight of std. Packing Unit	0.45 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	1.5 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	2.5 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	17.5 A
Nominal cross section	1.5 mm ²
Short-time current	0.18 kA
Rated surge voltage	8 kV
Degree of pollution	3

Ratings - ATEX

ATEX Standard	EN 60079-7
ATEX Nominal Voltage U_n	500 V
ATEX Nominal Current I_n	15 A
ATEX Cross Sec. Flexible Max.	1.5 mm ²

Ratings - CSA

CSA Standard	
B - CSA Nominal Voltage U_N	V
B - CSA Nominal Current I_N	A
B - CSA Wire Min	AWG
B - CSA Wire Max	AWG

Ratings - UL

UL Standard	UL 1059
B - UL Nominal Voltage U_N	600 V
B - UL Nominal Current I_N	15 A
B - UL Wire Min	24 AWG
B - UL Wire Max	14 AWG