



PQ2.5-2T+IS

Terminal Type - PQ2.5-2T+IS , Multi level terminal block, connection method: Push-in connection, nominal voltage: 1000 V , nominal current: 24 A , Rated cross-section - 2.5 mm² , number of connections: 4, cross-section: 0.08 mm² - 4 mm², AWG : 24-12 , mounting type: TS 35/7.5, TS 35/15



Approvals



General Information

Product Name	PQ2.5-2T+IS
Connection Method	Push In Connection
Rating	1000 V/24 A/2.5 mm ² /NAP Nm
HSN Number	8904476705365
Standard Packing Qty(in No)	100
Country Of Origin	India
Screw thread	NAP

Dimensions & Weight

Width	5 mm	0.2 inch
Length	73.17 mm	2.88 inch
Height	47 mm	1.85 inch
Weight of std. Packing Unit	1.24 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.08 mm ²
Conductor cross section flexible max	2.5 mm ²
Conductor cross section solid min	0.08 mm ²
Conductor cross section solid max	4 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	24 A
Nominal cross section	2.5 mm ²
Short-time current	0.3 kA
Rated surge voltage	8 kV
Degree of pollution	3

