



## PQ4-2T

Terminal Type - PQ4-2T, Multi level terminal block, nominal voltage: 1000 V, nominal current: 28 A, connection method: Push in type, number of connections: 4, cross section: 0.08 mm<sup>2</sup> - 6 mm<sup>2</sup>, mounting type: TS 35/7.5, TS 35/15.



### Approvals



### General Information

|                             |                                       |
|-----------------------------|---------------------------------------|
| Product Name                | PQ4-2T                                |
| Connection Method           | Push In Connection                    |
| Rating                      | 1000 V/28 A/4 mm <sup>2</sup> /NAP Nm |
| HSN Number                  | 8904476700841                         |
| Standard Packing Qty(in No) | 50                                    |
| Country Of Origin           | India                                 |
| Screw thread                | NAP                                   |

### Dimensions & Weight

|                             |         |           |
|-----------------------------|---------|-----------|
| Width                       | 6 mm    | 0.24 inch |
| Length                      | 99.3 mm | 3.91 inch |
| Height                      | 49.6 mm | 1.95 inch |
| Weight of std. Packing Unit | 1.07 Kg |           |

### Material Data

|                     |               |
|---------------------|---------------|
| Insulating Material | Polyamide 6,6 |
| Standard Colour     | Gray          |
| Colour Variants     |               |

### Rated Conductor Size

|                                      |                      |
|--------------------------------------|----------------------|
| Conductor cross section flexible min | 0.08 mm <sup>2</sup> |
| Conductor cross section flexible max | 4 mm <sup>2</sup>    |
| Conductor cross section solid min    | 0.08 mm <sup>2</sup> |
| Conductor cross section solid max    | 6 mm <sup>2</sup>    |

## Ratings - IEC

|                                  |                   |
|----------------------------------|-------------------|
| Connection in acc. with standard | IEC 60947-7-1     |
| Nominal Voltage $U_n$            | 1000 V            |
| Nominal Current $I_n$            | 28 A              |
| Nominal cross section            | 4 mm <sup>2</sup> |
| Short-time current               | 0.48 kA           |
| Rated surge voltage              | 8 kV              |
| Degree of pollution              | 3                 |

