


PQ6-2X2

Terminal type - PQ6-2X2, Multi conductor feed-through terminal block, nominal voltage: 1000 V, nominal current: 41 A, connection method: Push in type, number of connections: 4, Rated cross section: 6 mm² , cross section: 0.2 mm² - 10 mm², mounting type: TS 35/7.5, TS 35/15.



Approvals



General Information

Product Name	PQ6-2X2
Connection Method	Push In Connection
Rating	1000 V/41 A/6 mm ² /NAP Nm
HSN Number	8904476705389
Standard Packing Qty(in No)	50
Country Of Origin	INDIA
Screw thread	NAP

Dimensions & Weight

Width	8 mm	0.31 inch
Length	98.6 mm	3.88 inch
Height	42.9 mm	1.69 inch
Weight of std. Packing Unit	1.36 Kg	

Material Data

Insulating Material	Polyamide 6,6
Standard Colour	Gray
Colour Variants	Red , Yellow , Blue , Black , Green , Khakhi ,

Rated Conductor Size

Conductor cross section flexible min	0.2 mm ²
Conductor cross section flexible max	6 mm ²
Conductor cross section solid min	0.2 mm ²
Conductor cross section solid max	10 mm ²

Ratings - IEC

Connection in acc. with standard	IEC 60947-7-1
Nominal Voltage U_n	1000 V
Nominal Current I_n	41 A
Nominal cross section	6 mm ²
Short-time current	0.72 kA
Rated surge voltage	8 kV
Degree of pollution	3

