


## SQ10-1X2

Terminal Type - SQ10-1X2 , Multi conductor feed through terminal block, nominal voltage: 1000 V, nominal current: 57 A, connection method: Spring Cage connection, number of connections: 3, cross section: 0.2 mm<sup>2</sup> - 16 mm<sup>2</sup>, AWG 24-6 , mounting type: TS 35/7.5, TS 35/15.



### Approvals



### General Information

|                             |                                        |
|-----------------------------|----------------------------------------|
| Product Name                | SQ10-1X2                               |
| Connection Method           | Spring Cage Connection                 |
| Rating                      | 1000 V/57 A/10 mm <sup>2</sup> /NAP Nm |
| HSN Number                  | 8904476701282                          |
| Standard Packing Qty(in No) | 25                                     |
| Country Of Origin           | INDIA                                  |
| Screw thread                | NAP                                    |

### Dimensions & Weight

|                             |        |           |
|-----------------------------|--------|-----------|
| Width                       | 10 mm  | 0.39 inch |
| Length                      | 99 mm  | 3.9 inch  |
| Height                      | 48 mm  | 1.89 inch |
| Weight of std. Packing Unit | 0.9 Kg |           |

### Material Data

|                     |                                                |
|---------------------|------------------------------------------------|
| Insulating Material | Polyamide 6,6                                  |
| Standard Colour     | Gray                                           |
| Colour Variants     | Red , Yellow , Blue , Black , Green , Khakhi , |

### Rated Conductor Size

|                                      |                     |
|--------------------------------------|---------------------|
| Conductor cross section flexible min | 0.2 mm <sup>2</sup> |
| Conductor cross section flexible max | 10 mm <sup>2</sup>  |
| Conductor cross section solid min    | 0.2 mm <sup>2</sup> |
| Conductor cross section solid max    | 16 mm <sup>2</sup>  |

## Ratings - IEC

|                                  |                    |
|----------------------------------|--------------------|
| Connection in acc. with standard | IEC 60947-7-1      |
| Nominal Voltage $U_n$            | 1000 V             |
| Nominal Current $I_n$            | 57 A               |
| Nominal cross section            | 10 mm <sup>2</sup> |
| Short-time current               | 1.2 kA             |
| Rated surge voltage              | 8 kV               |
| Degree of pollution              | 3                  |

## Ratings - ATEX

|                               |                    |
|-------------------------------|--------------------|
| ATEX Standard                 | EN 60049-7         |
| ATEX Nominal Voltage $U_n$    | 500 V              |
| ATEX Nominal Current $I_n$    | 51 A               |
| ATEX Cross Sec. Flexible Max. | 10 mm <sup>2</sup> |

## Ratings - CSA

|                               |     |
|-------------------------------|-----|
| CSA Standard                  |     |
| B - CSA Nominal Voltage $U_N$ | V   |
| B - CSA Nominal Current $I_N$ | A   |
| B - CSA Wire Min              | AWG |
| B - CSA Wire Max              | AWG |

## Ratings - UL

|                              |         |
|------------------------------|---------|
| UL Standard                  | UL 1059 |
| B - UL Nominal Voltage $U_N$ | 600 V   |
| B - UL Nominal Current $I_N$ | 65 A    |
| B - UL Wire Min              | 24 AWG  |
| B - UL Wire Max              | 6 AWG   |